

Technical Data Sheet

Effective: 04/05/2017

Automotive Aftermarket Division

3M 36109/36110/36111 Perfect-It Gelcoat Light Cutting Compound + Wax

1) Part Numbers

36109 : 473ml 36110 : 946ml 36111 : 3.6l

2) Description and end uses

3M™ Perfect-It™ Gelcoat Medium Cutting Compound + Wax is designed to remove P800 and finer sand scratches with a 3M™ compounding pad. It is designed to work over a broad range of climates. Its non-gritty formula works on all types of gelcoat surfaces, leaving an extremely fine finish with easy clean up. To reduce compounding time refine sanding marks with 3M™ Trizact™ 1500 before compounding.

3) Physical Properties

Container	Various (See Above)
Colour	White
Flash Point - °C	No Flash @ 20°C, 38°C, 60°C or 93°C
Viscosity (CPS) Brookfield Viscometer	30,000 – 40,000 cps @ 25°C
Solids Content (Appx.)	Trade Secret
Solvent	14.5% VOC



Technical Data Sheet

Effective: 04/05/2017

4) Directions for Use

Directions for Use by Machine:

- 1. Apply material to a 2' x 2' area.
- 2. Use the buffing pad on the buffer to spread material to reduce slinging.
- 3. Buff area using a 3M Wool Compounding pad with buffer set between 1200 and 2000 rpm.
- 4. Buff area using light to medium pressure. As material begins to dry reduce pressure.

Directions for Use by Hand:

- 1. Apply material to a 1'x 1' area using a clean microfiber detailing cloth.
- 2. Rub gelcoat surface in a circular motion. Work the area until the material is gone. Do not allow product to haze.
- 3. Heavily oxidized surfaces may require multiple applications or application by machine.

5) Storage

Keep from freezing.

6) Safety

Refer to product label and safety data sheet for health and safety information before using the product.

7) Disclaimer

All statements, technical information and recommendations are based on tests we believe to be reliable but the accuracy or completeness thereof is not guaranteed. Please ensure before using our product that it is suitable for your intended use. All questions of reliability relating to this product are governed by the Terms of Sale subject, where applicable, to the prevailing law.



Technical Data Sheet

Effective: 04/05/2017

For Additional Health and Safety Information

Denmark

3M a/s Automotive Aftermarket Hannemanns Allé 53 2300 København S Tel: 43 48 01 00

3mkundeservicedk@mmm.com www.3MAuto.dk

Norway

3M Norge AS
Automotive Aftermarket
Kanalveien 2
2004 Lillestrøm
Telefon: 06384
www.3m.no/auto

kundeservice@mmm.com

Finland

Suomen 3M Oy
Automotive Aftermarket
Keilaranta 6
02150 Espoo
Tel: 09 5252 1
tilaukset@mmm.com

Sweden

www.3M.fi/autotuotteet

3M Svenska AB
Automotive Aftermarket
Bileftermarknad
19189 Sollentuna
Tel. 08-922100
kundservice@mmm.com
3M.se/bileftermarknad