


BRIGHT TECK

CONCENTRATED TEAK BRIGHTENER STEP N° 2



BRIGHT TECK has a very powerful penetrating action for the second stage in the restoration of a teak deck.

BRIGHT TECK should be used immediately after the teak cleaner **SUN TECK**.

BRIGHT TECK is a controlled acid-based product which uses a combination of active substances to restore teak decks to their original colour.

BRIGHT TECK does not affect in any way the caulking, fibreglass and paint when the advise usage are respected.

BRIGHT TECK removes greyish stains cause by severe weather, salt water and pollution, restoring the teak to its natural colour.

Technical Data :

- Physical state : fluid Liquid
- Density : 1055 g/l +/- 20 g/l.
- pH pur: 2.10 approx. (acidic)
- Colour : colourless

Ref. 639M - Bottle 1 litre
Ref. 639M.5 - Bottle 5 litres
Ref. 639M.10 - Bottle 10 litres
Shelf Life : 3 years

H315 Causes skin irritation. H318 Causes serious eye damage. P280 Wear protective gloves/protective clothing/eye protection/face protection. P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P102 Keep out of reach of children. Always carry out a test prior to use on the surface to be treated to determine suitability and the appropriate contact time. Components contain less than 5% of anionic surfactants and 5% or more but less than 15% of non ionic surfactants.

This document does not imply our responsibility as to specific applications. This data sheet can already, at this precise moment, be revised for reasons due to the legislation, the availability of components or experiences recently acquired. The last version of this data sheet, which is the only one valid, will be sent to you on simple request.

BRIGHT TECK is used as follows :

- Dilute 1 litre of product for 3 to 5 litres of water depending on the level of staining.
- First of all, wet the teak and the hull.
- It is advised to do not work to direct sunlight in order to avoid black stains on gelcoat and paint.
- Apply the solution evenly with a soft brush.
- Leave for 10 to 15 minutes.
- Do not rub.
- Rinse abundantly with a water jet.

Coverage for 1 litre of product : 5 to 7 m².



SAS MATT CHEM PRODUCT®
FRENCH MANUFACTURE
(92) Bagneux France
Tel : +33 (0) 1 42 53 73 73 – Fax : +33 (0) 1 47 35 27 28
Website : www.mattchem.com - www.mattchem.fr
email : info@mattchem.fr
January 2014