


GALVANY

GALVANIZATION ZINC SPRAY



GALVANY contains filing metals ensuring an exceptional anti-corrosion protection.

GALVANY has a very good adherence on oxidized, rusted or chrome surfaces.

GALVANY protects a longtime against corrosion.

GALVANY is stable against salt, water and high temperatures.

INSTRUCTIONS OF USE :

Spray **GALVANY** on a clean and dry surface at 20 to 25 cm from the surface.

Wait a few minutes and apply a second coat.
Time of drying : 1 hour.

Advise : At the end of the use, not to forget to purge the aerosol upside down in order to avoid the stopping of the valve and pushbutton by the resins and lamellate metal.

Technical Data :

- Physical state : Viscous Liquid.
- Density : 970 g/l +/-20 g/l.
- Chemical reaction : Neutral.
- Flash Point : < 21 °C AFNOR closed cup.
- Odour : Characteristic of solvent.
- Colour : Silver

Ref. 597M - Aerosol 150ml
Shelf Life : 12 Months

H222 Extremely flammable aerosol. H229 Pressurized container: may burst if heated. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. EUH066 Repeated exposure may cause skin dryness or cracking. P102 Keep out of reach of children. P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking. P211 Do not spray on an open flame or other ignition source. P251 Pressurized container: Do not pierce or burn, even after use. P305 + P351 + P338 – IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P410 + P412 Protect from sunlight. Do no expose to temperatures exceeding 50°C/ 122°F.

This document does not imply our responsibility as to specific applications. This data sheet can already, at this precise moment, be revised for reasons due to the legislation, the availability of components or experiences recently acquired. The last version of this data sheet, which is the only one valid, will be sent to you on simple request.



SAS MATT CHEM PRODUCT®
FRENCH MANUFACTURE
(92) Bagneux France
Tel : +33 (0) 1 42 53 73 73 – Fax : +33 (0) 1 47 35 27 28
Website : www.mattchem.com - www.mattchem.fr
email : info@mattchem.fr
January 2014