

## TECHNICAL BULLETIN

## **OXIDATION REMOVER**

Removes moderate oxidation, scratches, stains and tough water spots on all fiberglass, gel coat, marine or RV surfaces. Restores color by effectively removing degration.

Part #:	M-4916 – 16 oz M-4901 – 1 gallon
Packaging:	16 oz 6 per case 1 gallon – 4 per case
Features:	<ul> <li>A heavy duty gel coat cleaner enriched with feeder oils to protect and lubricate the finish</li> <li>Effectively removes surface degradation, restores color and brings out the best in older fiberglass</li> </ul>
pH:	N/A
Paintable:	Yes
Dilution:	RTU (Ready to use)
Application Method:	Rotary, Orbital, DA and Hand
Directions:	FOR MACHINE USE: SHAKE WELL. Always apply in the shade on a cool surface. Working one section at a time, dispense product on
	washed surface. Working one section at a time, dispense product on washed surface (when working with a new buffing pad, apply a small amount of product, in the shape of an X on the pad itself). Do not apply to vinyl or rubber surfaces. Using moderate pressure on the buffer, spread the product evenly over the surface with overlapping movements, to ensure uniform coverage. Work product until nearly dry. Immediately wipe dry with a separate clean, 100% cotton terry towel. (For best results use a high-speed rotary buffer with a mirror glaze Cutting Pad.) <b>FOR USE BY HAND. SHAKE WELL.</b> Always apply in the shade on a cool surface. Working one section at a time, dispense a small amount on a 100% cotton, terry cloth towel or applicator pad and rub thoroughly into the surface. Immediately wipe dry with a separate clean 100% cotton, terry cloth towel.

## FOR ADDITIONAL SAFETY INFORMATION, CONSULT MSDS KEEP OUT OF REACH OF CHILDREN