

# PRO-LIFT

# SUSTAINABLE DEVELOPMENT

# LIQUID POLISH P.T.E.F® BASED

**PRO-LIFT** is a polish containing P.T.E.F. The P.T.E.F. is a resin, which has a very low coef- Well shake before use. ficient of friction.

- Excellent resistance to U.V. rays allowing to slow down the fading and the oxidation.
- Leaves a protective film allowing to decrease the friction and the wear of gelcoat and paint.
- Makes it possible to repel salt and deposits.
- Brings back shine.

## Technical data:

Physical state: Liquid

Colour: white Relative density: 1

Chemical reaction: Neutral

### Instructions of use:

Apply on a dry and clean surface. Take care to not apply on hot surface or in direct sunlight. Apply evenly with a clean cloth to a small area in a circular motion while polish is wet. Let dry a few moments. **PRO-LIFT** will quickly dry to a haze. Wipe off haze using another clean, dry cloth.



Ref. 347M - Bottle 500ML

Shelf Life: 3 years

P102 Keep out of reach of children. P262 Do not get in eyes, on skin, or on clothing. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing. P301+330+331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. EUH 066 - Repeated exposure may cause skin dryness or cracking. Always make beforehand, a test with the surface to be treated to determine the compatibility and the time of contact suited

This document does not imply our responsability as to specific applications. This data sheet can already, at this precise moment, be revised for reasons due to the legislation, the availability of components or experiences recently acquired. The last version of this data sheet, which is the only one valid, will be sent to you on simple request.



SAS MATT CHEM PRODUCT® FRENCH MANUFACTURE (92) Bagneux France

Tel: +33 (0) 1 42 53 73 73 - Fax: +33 (0) 1 47 35 27 28 Website: www.mattchem.com - www.mattchem.fr

email: info@mattchem.fr January 2017