

LUBMARE

EXTREME-PRESSURE WATER RESISTANT GREASE



SPECIFICATIONS

- Compliant with ISO 6743-9
- Compliant with DIN 51 502
- Compliant with NATO classification RG-468 and G-460

ADVANTAGES

- LUBMARE exhibits negligible deterioration with age. After numerous months of application, LUBMARE does not soften.
- Very good anti-wear and extreme pressure properties.
- LUBMARE adheres well to metal which ensures good sealing.
- LUBMARE can be easily applied by brush.

TECHNICAL DATA

TYPICAL CHARACTERISTICS	METHODS	UNITS	
NLGI grade	ASTM D 217/DIN 51 818	-	1.5
Color	Visual	-	Green
Appearance	Visual	-	Tacky
Operating temperature range		°C	-20 to 110
Penetration at 25°C	ASTM D 217/DIN51 818	0.1 mm	310 - 340
Four ball weld load	DIN 51 350-4	daN	315
Anti-rust performance SKF- EMCOR	DIN 51 802/IP220/NFT 60-135/ISO 11007	rating	0-0
Dropping point	IP 396/DIN ISO 2176	°C	> 140
Protection period	E.A.P.	months	> 18

Above characteristics are mean values given as an information.

Ref. 640M - Can 150ml
Ref. 640M.05 - Can 500ml
Ref. 640M.5 - Bucket 5Kgs
Ref. 640M.F - Bucket 25 Kgs

Shelf Life : 3 years

H319 Causes serious eye irritation.
P280 Wear eye protection/face protection.
P102 Keep out of reach of children.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes.
Remove contact lenses, if present and easy to do. Continue rinsing.

Always make beforehand, a test with the surface to be treated to determine the compatibility and the time of contact suited.

This document does not imply our responsibility as to specific applications. This data sheet can already, at this precise moment, be revised for reasons due to the legislation, the availability of components or experiences recently acquired. The last version of this data sheet, which is the only one valid, will be sent to you on simple request.



SAS MATT CHEM PRODUCT®
FRENCH MANUFACTURE
37, rue de Fontenay (92) BagneuxFrance
Tel : (33) 1 42 53 73 73 – Fax : (33) 1 47 35 27 28
www.mattchem.com - info@mattchem.fr
November 2020