

ARDOISE C01	SIENNE C03	SABLE C04	BLEU C05
IVOIRE C06	NOIR C08	MARRON C09	GRIS EXPRESS C10
BLANC C11	ROUGE C14	VERT GOLF C15	ICEBERG C21
GRIS PERLE C23	JAUNE RAL 1028 C24	GRIS TROPIC C25	

PERFORMANCE TESTS :

Non-slip resistance :

SRT test according to the **EN 13036-4** norm :
1,12 on dry surface, **0,67** on wet surface

Fire resistance :

According to NF EN 13501-1 : Cfl-s1


Other resistances :

Flexibility – Distortion : 40% before breakage

UV rays : very good resistance to UV rays

Very good resistance to natural chemical agents, oils, greases, hydrocarbons and salt water.

Excellent resistance to abrasion and impacts



Tests made by the Bridge and Roadway Agency laboratory from Angers – France

PONTS et CHAUSSEES D'ANGERS - LNE

TBSAFE 21

Non-slip covering – strong and comfortable - For intense pedestrian traffic

APPLICATIONS :

- Cockpit access
- Ship decks
- Machine environment
- Pedestrian traffic areas
- Workplace environment

CHARACTERISTICS :

Chemical composition : polyurethane elastomeric complex with high non-slip performances.

Thickness : 2,1 mm – **Weight :** 2,5 kg/sqm – Non abrasive flexible 800 microns granules.

Temperature resistance : from -30° to +80°C.

Ease of maintenance : clean regularly with water and traditional detergent. For factories or shops, it is recommended to use biodegradable detergents with a 9pH.

Storage : in the original packaging, protected from humidity. Manipulate with temperatures between +5° and +30°.

SIZES :

STRIP Self adhesive	BLISTER Self adhesive or plain	SHEET Self adhesive or plain	ROLL Plain
25 mm x 10 lm	1,28 m x 5 m	1,28 m x 0,90 m	600 mm x 10 lm
30 mm x 10 lm			
40 mm x 10 lm			
50 mm x 10 lm			
100 mm x 10 lm			
300 mm x 10 lm			
600 mm x 10 lm			